



PN-EN 13859-1:2010; PN-EN 13859-2:2010

Declaration of Performance

According to Annex of Regulation (EU) No. 305/2011
Nr DoP 1-1122015-08
for the product

Premium PRIVATE LABEL 140 / Eurovent **MAXI**

| | |
|---|--|
| 1. Product type: unique identification code of the product type | 1-1122015-08 |
| 2. Intended use or uses of the construction product | Underlay for discontinuous roofing and as underlay for walls (roof underlay, vapour permeable, watertight, for the pitched roofing also fully sheathed, and as housewrap or fasade membrane |
| 3. Manufacturer | Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13, 46-055 Przywory, Polska VAT PL 9372516153 |
| 4. Authorized representative | not relevant |
| 5. System or systems of assessment and verification of constancy of performance | System 3 |
| 6. Harmonized specification(s). Notified body(ies). | EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 1: Underlays for discontinuous roofing EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls Institut für textile Bau- und Umwelttechnik GmbH Institute for textile building and environment technology Gutenbergstr. 29, 48268 Greven, Germany, identification number: 0799, test report nr 1.1/18493/670.0.2.1-2006 |

7. Declared performance

| Characteristic | Harmonized technical specification | Values |
|--|--|----------------------------------|
| Reaction to fire | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | E |
| Resistance to water penetration | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | W1 |
| Tensile strength MD | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≥270 N/50 mm (+/- 85 N/50 mm) |
| Tensile strength CD | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≥210 N/50 mm (+/- 50 N/50 mm) |
| Elongation MD | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≤60% |
| Elongation CD | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≤60% |
| Tearing Resistance MD | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≥160 N (+/-30N) |
| Tearing Resistance CD | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≥150 N (+/-35N) |
| Flexibility at low temperatures | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | w -30 °C COMFORMING |
| Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat | | |
| Resistance to water penetration | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | W1 |
| Tensile strength MD change | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | <30% |
| Tensile strength CD change | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | <30% |
| Elongation MD change | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≤60% |
| Elongation CD change | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | ≤60% |
| Water vapor transmission | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | Sd=0,02m (+/-0,019m) |
| Hazardous substances | PN-EN 13859-1:2010; PN-EN 13859-2:2010 | Does not contain |

8. Declaration: the performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Przywory, 01.12.2015 r.

Marcin Świerta
President

