

## TECHNICAL DATA SHEET

### Eurovent **MULTI**

Strongly adhesive, solvent-free and odorless glue for general purpose, ideal for gluing vapor insulation, roofing membranes and foils inside and outside buildings, highly resistant to aging, very flexible and stretchy, susceptible to movements of the building - bonding joints. The adhesive is suitable for plastering and painting over.



PARAMETRER	UNIT	VALUE
Material		Solvent free poly - acrylic emulsion
Consistency		Pasty
pH value		Alkaline (7,8 - 8,2)
Application temp.	[°C]	-10 to +40
Temperature resistance	[°C]	-20 to + 80
Density	[kg/l]	1,02
Cardridge capacity	[ml]	310
Color		Blue
Cardboard	[pcs]	20
Pallet	[cardboards / pcs]	60 / 1 200

#### Advantages:

- Flexible and extensible
- Highly resistant to aging
- Susceptible to movement building
- Solvent-free, odorless

## Eurovent MULTI

### Application:

For gluing vapor barriers, roofing membranes, foils inside and outside the buildings, gluing joints. The adhesive is suitable for plastering and painting. Application temperature min./max. : -10 ° C to + 40 ° C. The surfaces of bonded parts should be clean and free of grease. Sealing Tube is applied as 6-8 mm thick adhesive line, on the solid, absorbent substrate. Rough surfaces will be leveled by the sealing compound. Hardening time for moist surfaces maybe increased significantly. For sheets with diffusion properties, we recommend wet-application, in which the fleece side of the connection sheet will be pressed on until 2-3 mm thickness, and therefore will be embedded into the soft sealing compound. For dry-application a ventilation time of minimum 24 hours is required, in order to reach the required level of hardening. The PE-sheet with non-diffusion properties can be safely bonded, by applying increased pressure. Secure and safe bonding requires clean, dust and oil free surfaces, which are stable and mostly dry.

### Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. The Product should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 05/2020